

WARRANTY EXCLUSIONS AND LIMITATION OF LIABILITY

IF THE USER DOES NOT ACCEPT THE FOLLOWING TERMS, THE USER SHOULD NOT USE THE SAFEAIR BADGES AND COLOR COMPARATORS.

Seller warrants that, for the lesser of one (1) year or the shelf-life provided on the Seller's product, its packaging or its literature, its products shall conform to the description of such products as provided on the Seller's product, its packaging or its literature. THIS WARRANTY IS EXCLUSIVE, AND SELLER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Seller's warranties made in connection with this sale shall not be effective if Seller has determined, in its sole discretion, that Buyer has misused the products in any manner, has failed to use the products in accordance with safe industry standards and practices, or has failed to use the products in accordance with Seller's written operating instructions, or other instructions furnished by Seller to Buyer.

Seller's sole and exclusive liability and Buyer's exclusive remedy with respect to products to Seller's satisfaction to be defective or nonconforming shall be replacement of such products without charge or refund of the purchase price, in Seller's sole discretion, upon the return of such products in accordance with Seller's instructions. All claims must be brought within one (1) year of shipment, regardless of their nature.

SELLER SHALL NOT IN ANY EVENT BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES OF ANY KIND RESULTING FROM ANY USE OR FAILURE OF THE PRODUCTS, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE INCLUDING, WITHOUT LIMITATION, LIABILITY FOR LOSS OF USE, LOSS OF WORK IN PROGRESS, DOWN TIME, LOSS OF REVENUE OR PROFITS, FAILURE TO REALIZE SAVINGS, LOSS OF PRODUCTS OF BUYER OR OTHER USE OF ANY LIABILITY OF BUYER TO A THIRD PARTY ON ACCOUNT OF SUCH LOSS, OR FOR ANY LABOR OR ANY OTHER EXPENSE, DAMAGE OR LOSS OCCASIONED BY SUCH PRODUCT INCLUDING PERSONAL INJURY OR PROPERTY DAMAGE UNLESS SUCH PERSONAL INJURY OR PROPERTY DAMAGE IS CAUSED BY SELLER'S GROSS NEGLIGENCE.

Warning: Keep out of reach of children, if ingested seek medical attention immediately.



2557 Production Rd.
Virginia Beach, VA 23454
Phone: (757) 431-2260 Fax: (757) 216-6209
E-mail: customerservice@morphtec.com

©1997, Morphix Technologies®
All rights reserved
Publication Number: KM4-28A.3-0606
US Patent Number: 6,284,198



Operating Instructions For
UDMH Dual Level Monitor
(Part Number: 382018)

Technical Summary

Physical Specifications:

Dimensions	(74 ± 1 mm) x (41 ± 1 mm) x (1 mm)
Weight	1.5 g
Refrigerated shelf life	1 year
Color change	orange to maroon

Sampling Parameters:

	Front	Back
Exposure dose:		
Badge	30 ppb·hr	10 ppb·hr
Badge with color comparator		10 - 700 ppb·hr
Minimum detectable limit (8 hours)	3.75 ppb	1.25 ppb
Maximum recommended sampling time	48 hours	48 hours
Minimum recommended sampling time	5 minutes	5 minutes
Relative humidity range	20% - 85%	20% - 85%
Face velocity range	10 - 150 cm/sec	10 - 150 cm/sec
Temperature range	60°F - 95°F	60°F - 95°F
Light effect - UV (direct sunlight)	no effect	no effect
Light effect - visible	no effect	no effect
Color stability	3 days	3 days

Applications:

The SafeAir 1,1-dimethyl hydrazine (UDMH) badge may be used for personnel or area monitoring for exposure times ranging from 5 minutes to 48 hours. For higher resolution, the SafeAir UDMH badge may be used in conjunction with the SafeAir UDMH color comparator (part number: 383003).

Cross Interferences:

High concentrations of hydrazine and monomethyl hydrazine are known interferences. No other interferences are known.

Introduction

Unsymmetrical dimethyl hydrazine (UDMH) is a fuming, colorless liquid with an amine-like odor. Exposure to UDMH may cause eye, and skin irritation, choking, chest pain, dyspnea, lethargy, nausea, anoxia, convulsions, and liver injury. OSHA exposure limit for UDMH is 0.5 ppm. NIOSH exposure limit for UDMH is 0.06 ppm (ceiling).

UDMH is a hypergolic rocket fuel ingredient, often used as a bipropellant in combination with a strong oxidizer. It is used in virtually all storable liquid rocket engines. Additionally, UDMH is a contaminant and a metabolite and breakdown product of daminozide.

Principle of Operation

The SafeAir UDMH badge is a monitoring system designed to indicate the presence of UDMH at concentrations below the permissible exposure limit. The SafeAir UDMH badge detects the presence of UDMH by forming a color change in the shape of an exclamation mark inside the triangle. This indication is produced by a color-forming reaction, which occurs when UDMH reacts with a flat indicator layer. The SafeAir UDMH badge is a dual level badge. A color change may appear on the front and/or the backside of the badge, depending upon the exposure dose.

Operating Instructions

1. Remove the pouch from the refrigerator and allow it to warm to room temperature.
2. Remove the badge from its protective pouch.
3. For personnel monitoring, attach the badge near the user's breathing zone (i.e. the collar) with the front side exposed to the surrounding atmosphere.
4. For area monitoring, attach the badge to a stand and mount in a centralized area with the front side exposed to the surrounding atmosphere.
5. The exclamation mark appears within the triangle when UDMH is present. Please note that the exclamation mark will appear underneath the printed exposure dose (sensitivity).
6. To obtain the average concentration, divide the exposure dose (ppb-hr) by the exposure time in hours (hr).

Storage

The SafeAir UDMH badge should be refrigerated in its sealed bag at all times.

Benefits

1. Accurate Detection: The SafeAir UDMH badge is designed to react selectively with UDMH with minimum interference from other substances.
2. Applications: The SafeAir badge may be used for personnel screening and for area monitoring or area mapping.
3. Ease of Use: The SafeAir badge is a direct-read device that gives immediate, on-site results.

Other Available Monitors

1. SafeAir Badges:

Aniline	Formaldehyde	Nitrogen Dioxide
Aromatic Isocyanates	Hydrazine	Ozone
Carbon Dioxide	Hydrides	Phosgene
Carbon Monoxide	Hydrogen Chloride	Sulfur Dioxide
Chlorine/Chlorine Dioxide	Hydrogen Sulfide	
Dimethyl Amine	Mercury	
2. SafeAir Color Comparators:

Arsine ¹	Hydrazine	Phosphine ¹
Carbon Dioxide	Hydrogen Chloride	TDI ⁴
Chlorine	MMH ³	
Chloroformates ²	Phosgene	
Diborane ¹	Phosgene ext. range	

If you require SafeAir monitors for a chemical hazard not listed, please contact Morphix Technologies® for a free compound consultation at (800) 808-2234.

¹ To be used with the SafeAir hydrides badges

² To be used with the SafeAir phosgene badges

³ To be used with the SafeAir hydrazine dual level badges

⁴ To be used with the SafeAir aromatic isocyanates badges